

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 926 892 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
30.06.1999 Bulletin 1999/26

(51) Int. Cl.⁶: H04N 7/088

(21) Application number: 98310734.3

(22) Date of filing: 24.12.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 26.12.1997 JP 36893897
26.12.1997 JP 36893997

(71) Applicants:
• Matsushita Electric Industrial Co., Ltd.
Kadoma-shi, Osaka 571-8501 (JP)
• Information Broadcasting Laboratories, Inc.
Taito-ku, Tokyo 111-0035 (JP)


(72) Inventors:
• Kataoka, Mitsutero
Fujisawa-shi, Kanagawa-ken 251-0002 (JP)
• Machida, Kazuhiro
Inzai-shi, Chiba-ken 270-1356 (JP)
• Harada, Takenosuke
Tsuzuki-ku, Yokohama 224-0029 (JP)

(74) Representative:
Senior, Alan Murray
J.A. KEMP & CO.,
14 South Square,
Gray's Inn
London WC1R 5LX (GB)

(54) Video clip identification system unusable for commercial cutting

(57) A tagged scene of a video stream transmitted from a first to second stations in television broadcasting system is collected while preventing the tags from being used for commercial cutting (i.e., indiscriminate tagged scene cutting). The first station generates for each scene a tag includes a category, a location for use in locating a beginning of the scene and a length. A second station obtains a desired category from the user. Detecting a tag in the video stream, if the category coincides with the desired category, the second station clips from the video stream a part of the length defined in the tag from a position located by using the location. Five solutions are disclosed: removing the length information from tag; inserting counterfeit tags; the first station encoding a part of tag and the second station decoding the encoded part; the first station encoding the category and sending a category-encoded category table the second station; and a syndrome of a combination of said category and a parameter is used as an encoded category. The parameter may be used as subcategory and/or super-category.

FIG. 1



EP 0 926 892 A2

Description

[0001] The invention generally relates to a television system and more particularly to a system for and method of identifying a part (clip) of a video stream, the system and method being difficult to use for a commercial cutting function. The system and the method is applicable to a television system that permits the user to collect a variety of video clips such as program previews, commercials, representative scenes of a program and so on.

[0002] Recently, television (TV) broadcasting systems have increased channels in number. This often causes the user to find a difficulty in selecting programs to watch. In order to facilitate the selection of programs, broadcasting parties deliver program presentation scenes, program previews and so on between programs. Engineers of next generation broadcasting system are examining video environment in which the receiver automatically stores incoming program presentation scenes so as to enable the user to select programs meeting the user's taste without suffering from a flood of information. These environments will permit the user to search the stored program presentation scenes for favorite programs. In these environments, a television receiver can automatically record a highlight scene in each program, permitting the user to find a program he or she want by searching the recorded scenes. Also, if the user likes automobiles for example, he or she can control the television receiver to automatically accumulate commercials of automobiles to form a visual catalogue of automobiles.

[0003] The receiver automatically accumulating only particular programs or particular scenes is achieved by the broadcasting side attaching identifying codes to broadcast programs and scenes and by the receiver identifying desired programs and scenes through the identifying codes. Specifically, the broadcasting side attaches tags to parts of a transmitted video stream such as e.g., program presentation scenes, commercials and program previews (i.e., includes in the transmitted video stream a tag or data set for each video part spacing a predetermined fixed period or a period specified in the tag after the video part). This enables the receiver to identify the video part by using associated tags, permitting the receiver to accumulate desired ones of the tagged scenes.

[0004] However, these tags also permit the receiver to easily remove or cut commercials and program presentation scenes inserted in the program in itself (commercial cutting). This is very disadvantageous for the sponsors to the program.

[0005] It is an object of the invention to provide techniques for collecting desired parts or scenes of a video stream by attaching a tag to each of the desired parts so as to prevent the tags from being used for commercial cutting (or information deletion, from the video stream, based on the tags associated with the commercial

scenes).

[0006] According to the principles of the invention, a method of and system for collecting a tagged scene of a video stream transmitted from a first station to second stations in television broadcasting system while preventing tags from being used for commercial cutting (i.e., indiscriminate tagged scene cutting) is provided. The first station generates a tag for the scene. The tag includes a category of the scene, a location for use in locating a beginning of the scene and a length of the scene. The first station makes an arrangement to prevent the tag from being used for commercial cutting; and insert the tag in the video stream at the position located by using the location.

[0007] The location in time may be either an interval between the insertion of the tag and the transmission of the scene or a relative time with respect to a reference time. The location may be a fixed period.

[0008] A second station obtains a desired category from the user; detects a tag in the video stream; makes a test to see if the category coincides with the desired category; and if so, clipping from the video stream a part of a length defined by the length of the scene from a position located by using the location in such manner as accords with the arrangement.

[0009] In a first embodiment, the length information is removed from the tag. In this case, the second station clips a largest one of a plurality of standardized lengths.

[0010] In a second, one or more counterfeit tag is inserted in the video stream. The counterfeit tags includes false data.

[0011] In a third, the first station encodes one of the category, the location and the length through a one-way function and uses the encoded one in place of the original one. The second station decodes the encoded one into a decoded one and uses the decoded one.

[0012] In a fourth embodiment, for each of possible categories the first station further sends a set of the category and the encoded category to the second stations before inserting the tag. The second station receives the sets from the first station; and if the category of the detected tag coincides with the encoded category associated by the set with the desired category, clips the above-mentioned part from the video stream.

[0013] In a fifth embodiment, a syndrome of a combination of the category and a parameter is used as the encoded category. In the first station, a list of subcategories is made for a desired one of possible categories; a syndrome for a combination of the desired category and each of the subcategories is calculated by using each of the subcategories as the parameter; a table of the category, the subcategories, and corresponding syndromes is sent to the second stations. The second station stores the received table and uses the syndromes as the encoded categories and the subcategories as the categories.

[0014] Also, the first station may create a super-category comprising a list of categories; find a syndrome for

a combination of the super-category and each of the categories of the list by using each of the categories of the list as the parameter; send the list for the super-category to the second stations; and use the syndromes as the encoded categories.

[0015] The features and advantages of the present invention will be apparent from the following description of an exemplary embodiment of the invention and the accompanying drawings, in which:

FIG. 1 is a diagram showing a television (TV) broadcasting network or system which has incorporated a system for collecting desired video scenes or clips in accordance with the principles of the invention;

FIG. 2 is a diagram showing an exemplary structure of a tag inserted in the video stream;

FIG. 3 is a diagram illustrating one way of sending tags and the way of identifying a video scene by using a tag;

FIG. 4 is a diagram illustrating another way of sending tags;

FIG. 5 shows an exemplary tag created and an exemplary tag-attaching operation executed in a TV system 1 that uses tags without length information in accordance with the principles of the invention

FIG. 6 is a flow chart showing an operation executed by the computer 24 in response to a creation of a tag in accordance with the principles of the invention;

FIG. 7 is a flow chart showing an operation executed by the computer 24 in response to a creation of a tag in accordance with the principles of the invention;

FIG. 8 is a diagram showing an exemplary counterfeit tag created in a second illustrative embodiment;

FIG. 9 is a flow chart showing an exemplary operation executed by the computer 24 in responsive to a creation of a tag in accordance with a third illustrative embodiment of the invention;

FIG. 10 is a diagram showing an arrangement of a video stream processor 42a used in place of the corresponding processor 42 of FIG. 1 in the third embodiment;

FIG. 11 is a diagram showing an arrangement of a video stream processor 42b used in place of the corresponding processor 42 of FIG. 1 in the fourth embodiment;

FIG. 12 is an exemplary category vs. encoded category table transmitted from the broadcasting party 2 to the TV receiver 4;

FIG. 13 is a diagram showing an operation of preparing the category-encoded category table 440 in accordance with the principles of the invention;

FIG. 14 is a flow chart showing an exemplary operation executed by the computer 24 in responsive to a creation of a tag in accordance with a fifth illustrative embodiment of the invention;

FIG. 15 is a flow chart showing an operation executed by the controller 48 in response to a reception of the clip collection command with a category specified;

FIG. 16 is an exemplary category vs. encoded category table transmitted from the broadcasting party 2 to the TV receiver 4 in a sixth embodiment of the invention;

FIG. 17 is a diagram showing an exemplary tag containing a syndrome in the coded or encrypted category field;

FIG. 18 is a diagram showing an exemplary category vs. encoded category table;

FIG. 19 is a diagram showing an example of a category list for a super-category "outdoor"; and

FIG. 20 is a diagram showing a table comprising a category, subcategories of the category, and corresponding syndromes.

[0016] Throughout the drawing, the same elements when shown in more than one figure are designated by the same reference numerals.

[0017] FIG. 1 is a diagram showing a television (TV) broadcasting network or system which has incorporated a system for collecting desired video scenes or clips in accordance with the principles of the invention. In FIG. 1, the TV broadcasting network 1 comprises broadcasting facilities 2 for transmitting a broadcast stream including a video stream, a transmission media 3 through which the broadcast stream is delivered, and a multiplicity of TV receiver systems (or systems incorporating a TV tuner) 4.

[0018] The broadcasting facilities 2 comprises a TV transmitter 20 and a video-editing computer 24 that permits the operator to enter additional information (e.g., tags) to be included in a completed TV program (or a TV program which has been edited and compiled with commercials of the sponsors to the TV program and which is ready for transmission). The TV transmitter 20 includes a transmission controller 22 for controlling the TV transmitter 20.

[0019] On the other hand, the TV receiver systems 4 at least comprises a tuner 40 for selecting a specified one of the received channels; a transport processor 41 for IF (intermediate frequency) processing and demodulating the output signal from the tuner 40 into a video stream and an audio stream; a video stream processor 42 for extracting the additional information in the video stream from the transport processor 41 and for extracting or clipping a specified video scene (specified by a tag included in the additional information) from the video stream; I/O devices 46 for permitting the user to enter a command and data for the TV receiver system; a mass storage device 47 for storing collected video scenes (or clips); and controller for controlling the above-mentioned elements 40 through 42, 46 and 47. The mass storage device 47 may be a hard disc device or a rewritable optical disc device. If the TV receiver system 4 is a

TV receiver, the system 4 further comprises a video processor 43 for providing a video output signal; an audio processor 44 for providing an audio output signal; and video and audio output devices. Bus lines 49 interconnect the elements 40 through 44, and 46 through 48.

[0020] It is noted that the transmission media 3 may be a terrestrial or satellite radio wave and/or cables. Also, the TV receiver system 4 may be any system having a TV tuner: e.g., a TV set, a video tape or cassette recorder, a rewritable optical disc, various kinds of set-top boxes, a computer with a tuner, other various information and/or communication system, etc. Basic concept of the invention

[0021] FIG. 2 is a diagram showing an exemplary structure of a tag inserted in the video stream. FIG. 3 is a diagram illustrating the way of identifying a video scene by using a tag. In FIG. 2, a tag 1 at least comprises a scene ID (or title) 10 for the scene defined by the tag, a category 11 into which the scene defined by the tag is classified, a location 12 information used for finding the start time of the scene, and the length 13 of the scene.

[0022] The location 12 is preferably expressed by a time period that equals to the difference between the start time of the scene and the transmission time of the tag which precedes the scene start time. In other words, the tag has to be transmitted earlier than the scene start time by the period specified by the location 12 as shown in FIG. 3.

[0023] In FIG. 3, a tag with a scene ID of "PRG.REP" is transmitted D1 sec before a representative scene of a program segment "PRG.A1" whose period of time is L1 sec. Tags "CM1" and "CM2" are transmitted D2 and D3 sec before commercials CM1 and CM2 whose length are L2 and L3 sec, respectively. A tag with a scene ID of "PRG.A2" is transmitted D4 sec before a program segment "PRG.A2" whose length is L1 sec.

[0024] Alternatively, the interval between the scene start time and the tag transmission time (hereinafter referred to as "the offset interval") may be set to a fixed period of time, say, D sec. In this case, each tag has to be transmitted D sec before the scene associated with the tag; and the location 12 may be omitted.

[0025] It is noted that the value of the location field 12 of a tag may be expressed as the scene start time Ti measured from a reference time T set in the video stream as shown in FIG. 4 instead of using the interval between the scene start time and the tag transmission time (Di in FIG. 3).

[0026] Five inventive techniques for attaching a tag to a desired video scene so as to prevent the tags from being used for commercial cutting will be described in the following.

Removing the length information from tag (Embodiment I)

[0027] FIG. 5 shows an exemplary tag created and an

exemplary tag-attaching operation executed in a TV system 1 that uses tags without length information in accordance with the principles of the invention. In FIG. 5, the operator searches a completed TV program (or a TV program which has been edited and compiled with commercials of the sponsors to the TV program and which is ready for transmission) and finds a desired scene in step 100. The operator creates a tag 1a without length information 13 for the found scene in step 101. The operator makes a test in step 102 to see if the end of the program is reached. If not, the operator returns to step 100. If the end of the program has been reached in step 102, then the operator ends the operation.

[0028] It is noted that in response to a creation of a tag in step 101, the computer 24 automatically inserts the created tag in an appropriate position in the TV program in a timing as shown in FIG. 3 or 4 in step 103. The insertion of tags are achieved either by blanking interval multiplexing in case of analog TV system or by time-division multiplexing in case of digital TV system.

[0029] If the user desires to utilize the video scene or clip collection function, the user is asked which category of information he or she wants. For this purpose, the broadcasting facility operator preferably sends a category list from which the user is permitted to select a category; the controller 48 stores the category list either in the pass storage device 47 or in a nonvolatile memory within the controller 48; and in response to a request from the user, the controller 48 may display the category list on the display device included in the video & audio output devices 45. Alternatively, a message "the category of this scene is 'CAR'" may be included in the corresponding scene. This enables the user to know a key word to use for the selection of category, permitting the user to collect information on the car thereafter. Once the user issues a clip collecting command specifying a desired category, the controller 48 keeps collecting and accumulating the video scenes with the tags whose category is CAR in the mass storage device 47 till the user issues another command to terminate the clip collection function.

[0030] In this embodiment, the TV receiver 4 clips a predetermined length of video scene from the position specified by the value Di or Ti in the location field 12 in step 105 and stores the clipped video scene in the mass storage device 47 in step 106 as shown in FIG. 6. Since the duration or time period of commercials has been standardized into some period, the predetermined length is preferably set to the largest one of the standard periods. Doing this enables each of the tagged video scenes of a specified category to be clipped in the maximum standardized length which is equal to or longer than the real length of the video scene.

[0031] It should be noted that the permission of tagging commercials is solely determined by the sponsor. In other words, a tag should not be attached to a commercial as long as the sponsor of the commercial does

not permit the tagging to the commercial.

[0032] If this kind of tags were used for commercial cutting of a TV program, some of the tagged scenes might be clipped too much from the TV program. It is assumed that in order to cut the commercials, the user tries to remove all of the tagged scenes. Then, some of the commercials would remain unclipped at all because the tagging is not permitted to those commercials. Further, some portions of the program which are other than commercial might be clipped against the user's will if tags were attached to such the portions. These will result in a defective TV program so defective as to be unbearable to watch. Thus, removing the length information from tag provides us with a simplest but effective tagging technique that is unusable to commercial cutting.

Using counterfeit tags (Embodiment II)

[0033] In this embodiment, the operator creates a normal tag 1 as shown in FIG. 2 for each of the desired video scenes.

[0034] FIG. 7 is a flow chart showing an operation executed by the computer 24 in response to a creation of a tag in accordance with the principles of the invention. In response to a creation of a tag by the operator, the computer 24 is permitted to attach a counterfeit tag 1c as shown in FIG. 8 before and/or after the tag created by the operator. In FIG. 8, the scene ID field 10 and the category field 11 of counterfeit tag 1c have values that make no sense. Though the offset interval of the offset interval is set to D sec, the location fields 12 may be eliminated from the tags 1 if the locations 12 are set to D in all of the tags 1.

[0035] The operation of the TV receiver 4 is the same as in case of the first embodiment. That is, once the user issues a clip collecting command specifying a desired category, the controller 48 keeps collecting and accumulating the video scenes with the tags with the specified category in the mass storage device 47 till the user issues another command to terminate the clip collection function.

[0036] However, if the tags were used for commercial cutting, this results in the cutting of scenes tagged with the counterfeit tags as well as scenes tagged with tags attached by the operator, yielding a defective TV program.

[0037] It should be noted that the broadcasting party should not use a key word "commercial" or any identical key word for the category fields 11 associated with commercials. This would permit the user or a designer of the TV receiver 4 to easily discriminate the commercial scenes from other scenes.

Secret-key encrypting of a part of tag (Embodiment III)

[0038] In this embodiment, any of the category 11, the location 12, and the length 13 fields of a tag is encoded

through a first one way function (or encrypted with a secret key) in the computer 24 of the broadcasting facilities 2; and the encoded or encrypted value is decoded through a second one way function (or decrypted with the same secret key) in the TV receiver 4. A one-way function is such that the function can be evaluated efficiently, but its inverse cannot be evaluated. That is, for almost all images, it is infeasible to compute any preimage.

[0039] In this embodiment, the operator creates a normal tag 1 for a desired video scene. Responsively, the computer 24 operates as shown in FIG. 9 instead of executing the step 103 of FIG. 5. In FIG. 9, the computer 24 saves the value of a predetermined field, say, the location field of the created tag in step 410. In step 411, the computer 24 encrypts (or encodes) the predetermined field (the location field 12 in this example) of the created tag with a secret key Ks (with a first one-way function). In step 412 the computer attaches the encrypted (or encoded) tag to the program according to the saved value (the location 12 in this case). It is noted that if the encrypted or encoded field is not the location 12 field, there is no need of storing the value of the encrypted or encoded field and accordingly the step 410 can be omitted.

[0040] As seen from the above, the expression "encode X through a first one-way function into an encrypted X" means "encrypt X with a secret key into an encrypted X." The expression "decode the encoded X through a second one-way function into X" means "decrypt the encrypted X with the same secret key into the original X."

[0041] FIG. 10 is a diagram showing an arrangement of a video stream processor 42a used in place of the corresponding processor 42 of FIG. 1 in the third embodiment. The video stream processor 42a comprises a tag extractor 420 disposed in the video stream path from the transport processor 41; a decryptor or decoder 422 connected with the output of the tag extractor 420; and a scene clipper 428 disposed in the video stream path from the tag extractor 420 and connected with a decryptor 422 output and the bus 49. The scene clipper 428 has a key word register (KEY WORD REG.) 429.

[0042] In operation, if the user issues a clip collecting command specifying a desired key word, the key word is registered in the key word register 429 within the scene clipper 428. If the tag extractor 420 detects a tag, the extractor 420 extracts the value from the location 12 field of the tag and passes to the decryptor 422. The decryptor 422 decrypts the received value, i.e., an encrypted location with the same secret key as used in the encryption by the computer 24 into a decoded location value, which is passed to the scene clipper 428. The scene clipper 428 compares the value of the category field 11 with the value in the key word register 429. If the values coincide with each other, the scene clipper 428 clips the portion of a length defined by the

length field 13 after the location value from the decryptor 422 has been passed after the detection of the tag. The clipped scene is stored by the controller 48 in the mass storage device 47. If the two values are not the same, the scene clipper 428 does nothing for the tag.

[0043] Thus the video scenes of the specified category (or the category specified by the key word) are collected and stored in the mass storage device 47.

[0044] It is noted that though the decryption may be achieved by software, it is preferable to do the decryption by hardware, especially by an integrated circuit. Doing this causes the secret key used for the decryption to be hardly leaked.

[0045] In the above example, the location field 13 has been encrypted, any other field may be encrypted. However, any of the category 11, the location 12, and the length 13 fields of the tag is preferably encrypted. The above-mentioned encryption is achieved by using any suitable one way function.

Using a concealed category information (Embodiment IV)

[0046] The above-described embodiment has encrypted the value of any desirable field in the broadcasting party 2, and the receiver 4 has decrypted the encrypted value into the original value. In stead of doing this, the broadcasting party 2 encrypts the value of the category field 11 with a secret key; the receiver 4 also encrypts the key word specified by the user with the same secret key as used in the encryption in the broadcasting party 2; and the receiver 4 collects and stores only the scenes associated with the tags whose category field 11 has the value that coincides with the encrypted key word.

[0047] The operation of the computer is the same as in the just-described embodiment, and accordingly omitted.

[0048] FIG. 11 is a diagram showing an arrangement of a video stream processor 42b used in place of the corresponding processor 42 of FIG. 1 in the fourth embodiment of the invention. In FIG. 11, the video stream processor 42b comprises a tag extractor 420b disposed in the video stream path from the transport processor 41 for extracting the value of the category field 11 of a detected tag; an encryptor 430 for encrypting a key word received from the controller 48 into an encrypted key word; a comparator 432 for comparing the value from the tag extractor 420b with the encrypted key word; and a scene clipper 428b disposed in the video stream path from the tag extractor 420b and connected with the comparator 432 output and the bus 49.

[0049] In operation, if the user issues a clip collecting command specifying a desired key word, the controller 48 sends the key word to the key word encryptor of the video stream processor 42b. The key word encryptor 430 encrypts the key word with the same secret key as used in the encryption by the computer 24 into an

encrypted key word. The tag extractor 420b extracts the value of the category field 11 from a detected tag and pass the extracted value to the comparator 432. The comparator 432 compares the extracted value with the encrypted key word from the key word encryptor 430 to provide a flag indicative of whether the comparison is successful. If the flag is logical 1, the scene clipper clips the portion of a length defined by the length field 13 after the value of the location field 12 of the detected tag has been passed after the detection of the tag. The clipped scene is stored by the controller 48 in the mass storage device 47. If the flag from the comparator 432 is logical zero, then the scene clipper 428b does nothing for the tag.

[0050] Thus the video scenes of the specified category (or the category specified by the key word) are collected and stored in the mass storage device 47.

[0051] Though the encryption is preferably achieved by hardware, it is possible to execute the encryption by software. In order to achieve this, the key word encryptor 430 has to be replaced with an encrypted key word register for storing an encrypted version of the key word specified by the user. Further, if the user issues a clip collecting command specifying a desired key word, the controller 48 first encrypts the key word with the same secret key as used in the encryption in the computer 24, and sends the encrypted key word to the encrypted key word register within the video stream processor 42b.

[0052] Since there is no way of discriminating the tags for commercial scenes from the tags for the other scenes, using the tags of this embodiment will result in the cutting of all the tagged scenes, yielding a very defective TV program.

Transmitting a category vs. encoded category table (Embodiment V)

[0053] In the just described embodiment, the TV receiver 4 may use a category-encoded category table transmitted from the broadcasting party 2 instead of encoding the key word specified by the user. If encoding a category C_j ($j = 1, 2, 3 \dots N$) through a one-way function f provides an encoded category $f(C_j)$, the category-encoded category table 440 is expressed as shown in FIG. 12. In FIG. 12, it is assumed that for example:

$f(\text{CAR}) = \text{NC0iS3J}$

$f(\text{CAMERA}) = \text{LA0U3M}$

$f(\text{COSMETIC}) = \text{Lig9LDEy}$ and so on.

[0054] FIG. 13 is a diagram showing an operation of preparing the category-encoded category table 440 in accordance with the principles of the invention. In step 450, the operator makes a list of categories C_1, C_2, \dots, C_N , and the computer 24 responsively creates the category-encoded category table 440 by encoding each of the categories in the list. In step 451, the computer 24 sends the category-encoded category table 440 to the

TV receiver 4 and ends the operation.

[0055] FIG. 14 is a flow chart showing an exemplary operation executed by the computer 24 in responsive to a creation of a tag in accordance with a fifth illustrative embodiment of the invention. In FIG. 14, the computer 24 encodes the category field 11 of the created tag with the one-way function in step 455. In step 456, the computer 24 attaches the tag to the program according to the location 12 value.

[0056] FIG. 15 is a flow chart showing an operation executed by the controller 48 in response to a reception of the clip collection command issued with a category specified. In response to the reception of the clip collection command, the controller 48 obtains an encoded category associated with the specified key C_j word from the table 440 in step 455. In step 456, the controller 48 passes the obtained encoded category $f(C_j)$ to the video stream processor 42 and ends the operation. Responsively, if the value of the encrypted category field (not shown) of the detected tag coincides with the received encoded category $f(C_j)$ from the controller 48, the video stream processor 42 clips the length specified by the length 13 field after the period specified by the location 12 field of the detected tag has been elapsed after the detection of the tag. Otherwise, the video stream processor 42 does nothing for the tag.

[0057] In this way, the above-described operation is repeated till the user issues a collection termination command without letting the user know the category of any tag. An attempt to cut commercials or indiscriminate tagged scene cutting will result in a defective program.

[0058] The fifth embodiment, which executes encoding or encryption in only one element: i.e., the computer 24 within the broadcasting facilities 2 is more robust to key attacks than the fourth embodiment, which executes encoding in every station: i.e., the computer 24 within the broadcasting facilities 2 and the video stream processor 42 or the controller 48 within each TV receiver. Using a syndrome as a one way function f (Embodiment VI)

[0059] If a category C_j is expressed in a binary code, the binary-coded category is considered to be a linear code. Assuming the binary code of C_j to be B -bits long, the binary code of C_j is a B -dimension vector or a $(1, B)$ matrix: and accordingly denoted with a bold type like C_j . Then, for such a linear code C_j , there exists a parity check matrix H that satisfies:

$$C_j^T H = 0, \quad (1)$$

where A^T is a transposed matrix of a matrix A .

[0060] For an error vector (i.e., an arbitrary vector) e , letting $C_j + e = y_j$, an expression $s_j = y_j^T H$ is called a syndrome of the received symbol y_j (This is on the assumption that C_j has changed to y_j due to an error e during transmission). From equation (1),

$$s_j = (C_j + e)^T H = e^T H.$$

[0061] In other words, the syndrome of the sum of the category C_j and an arbitrary vector X (hereinafter, X is used in place of e), i.e., $(C_j + X)^T H$ (H is a parity check matrix for C_j) is equal to $X^T H$, which is independent of the value of the category C_j .

[0062] In a preferred embodiment, the following function:

$$s(C_j) = (C_j + X)^T H = X^T H \quad (2)$$

is used as an above-mentioned one-way function f .

[0063] In this specific embodiment, the category vs. encoded category table 540 is defined as shown in FIG. 16. In this table, the encoded category field contains $s(C_j) = X^T H$ (H is a parity check matrix for C_j). Also, each tag is defined as shown in FIG. 17. In FIG. 17, the encoded category field 11f contains $s(C_j) = X^T H$ (H is a parity check matrix for C_j). By using the table 540, the tags of the category specified by the user can be selected in the same manner as in the fifth embodiment.

[0064] The above defined function s has two interesting properties.

[0065] It should be first noted that using different values of X for an identical category enables each category C_j to have a plurality of values $X_{j,k}^T H_{j,k}$ ($k = 1, 2, \dots$, H_j is a parity check matrix for C_j). It is possible to express subcategories of C_j by respective quantities $X_{j,k}$.

[0066] FIG. 18 is a diagram showing an exemplary category vs. encoded category table 540a in which each category is permitted to have a plurality of values (these values may be used to express subcategories). In FIG. 18, {xxxx} is a binary code expression of a character string "xxxx". H_{car} , H_{camera} and $H_{sporting}$ are the parity check matrices for {car} and {camera}, {sporting} respectively. In this way, each category C_j is subdivided into subcategories $X_{j,k}$.

[0067] It should be also noted that a super-category which includes a plurality of categories is created by combining an identical quantity X_k with different categories. In order to achieve this, a list of categories that the super-category should include is made as shown in FIG. 19. In FIG. 19, a super-category "outdoor" includes categories "car", "sporting", and so on. Then a syndrome for each listed categories: e.g., $\{\text{outdoor}\}^T H_{car}$, $\{\text{outdoor}\}^T H_{sporting}$, etc. is calculated.

[0068] Though the encoded category field of the table 540a contains expressions like $\{\text{SEDAN}\}^T H_{CAR}$, the encoded category field actually contains binary codes. For this reason, it is preferable for the broadcasting side 2 to have a table that has the fields for a category (C_j), a subcategory (X), and the encoded category $X^T H$ as shown in FIG. 20.

[0069] The table 540a of FIG. 18 is transmitted from the broadcasting side 2 to the TV receivers 4 in advance. If subcategories and super-categories are to

be used, The tables 550 and 560 of FIG. 19 and 20 are preferably transmitted from the broadcasting side 2 to the TV receivers 4 in advance.

[0070] Many widely different embodiments of the present invention may be constructed without departing from the spirit and scope of the present invention. It should be understood that the present invention is not limited to the specific embodiments described in the specification, except as defined in the appended claims.

Claims

1. In a television broadcasting system wherein a first station transmits a video stream to second stations, a method, for use in the first station, of permitting the second stations to collect a scene within the video stream, the method comprising the steps of:
 - generating a tag for said scene, said tag including a category of said scene, a location for use in locating a beginning of said scene and a length of said scene;
 - making an arrangement to prevent said tag from being used for commercial cutting (i.e., indiscriminate tagged scene cutting); and
 - inserting said tag in said video stream at the position located by using said location.
2. In a television broadcasting system wherein a first station transmits a video stream to second stations, a method, for use in the second stations, of collecting a scene within the video stream, the method comprising the steps of:
 - obtaining from a user a desired category that the user desires;
 - detecting said tag in said video stream, said tag including a category of said scene, a location for use in locating a beginning of said scene and a length of said scene, said tag having been so arranged as to prevent said tag from being used for commercial cutting; and
 - if said category coincides with said desired category, clipping from said video stream a part of a length defined by said length of said scene from a position located by using said location in such manner as accords with said arrangement.
3. A method as defined in claim 1, wherein said step of making an arrangement comprises the step of removing said length from said tag.
4. A method as defined in claim 2, wherein said step of clipping from said video stream a part of a length comprises the step of clipping a part of a largest one of a plurality of standardized lengths.
5. A method as defined in claim 1 or 3, wherein said step of making an arrangement comprises the step of inserting at least one counterfeit tag in said video stream, said counterfeit tag including false data.
6. A method as defined in claim 1, 3 or 5 wherein said step of making an arrangement comprises the step of:
 - encoding one of said category, said location and said length through a one-way function; and
 - using said encoded one in place of said one.
7. A method as defined in claim 2, or 4 wherein one of said category, said location and said length through a one-way function has been encoded with a one-way function, and wherein said step of clipping from said video stream a part of a length further comprises the steps of:
 - decoding said one into a decoded one; and
 - using said decoded one in place of said one.
8. A method as defined in claim 1, wherein said step of making an arrangement comprises the steps of:
 - encoding said category into an encoded category through a one-way function;
 - using said encoded category in place of said category; and
 - for each of possible categories, sending a set of said category and said encoded category to said second stations before inserting said tag in said video stream.
9. A method as defined in claim 2, wherein said category of said detected tag has been encoded into an encoded category with a one-way function, and wherein said step of clipping from said video stream a part of a length comprises the steps of:
 - receiving a set of said category and said encoded category for each of possible categories; and
 - if said category of said detected tag coincides with said encoded category associated by said set with said desired category, clipping from said video stream said part.
10. A method as defined in claim 8, wherein said encoded category is a syndrome of a combination of said category and a parameter.
11. A method as defined in claim 10, further comprising the steps of:
 - making a list of subcategories for a desired one

of possible categories;
 find a syndrome for a combination of said
 desired category and each of said subcate-
 gories by using each of said subcategories as
 said parameter;
 send a table of said category, said subcate-
 gories, and corresponding syndromes to said
 second stations; and
 using said syndromes as said encoded cate-
 gories.

12. A method as defined in claim 10, further comprising the steps of:

creating a super-category comprising a list of
 categories;
 find a syndrome for a combination of said
 super-category and each of said list of cate-
 gories by using each of said list of categories as
 said parameter;
 send said list for said super-category to said
 second stations; and
 using said syndromes as said encoded cate-
 gories.

13. A method as defined in claim 9, wherein said encoded category is a syndrome of a combination of said category and a parameter.

14. A method as defined in claim 13, further comprising the step of:

receiving a table of said category, subcate-
 gories of said category and corresponding syn-
 dromes from said first station; and
 using said syndromes as said encoded cate-
 gories and using said subcategories as said cate-
 gories.

15. A method as defined in claim 13, further comprising the step of:

receiving a super-category list comprising a list
 of categories from said first station; and
 using said syndromes as said encoded cate-
 gories and using said super-category as one of
 said categories.

16. A system, within a first station in a television broad-
 casting system, for permitting a second station to
 collect a scene within a video stream from the first
 station, the system comprising:

means for generating a tag for said scene, said
 tag including a category of said scene, a loca-
 tion for use in locating a beginning of said
 scene and a length of said scene;
 means for preventing said tag from being used

for commercial cutting (i.e., indiscriminate
 tagged scene cutting); and
 means for inserting said tag in said video
 stream at the position located by using said
 location.

17. In a television broadcasting system wherein a first
 station transmits a video stream to second stations,
 A system, within the second station, for collecting a
 scene within a video stream from the first station,
 the method comprising:

means for obtaining from a user a desired cat-
 egory that the user desires;
 means for detecting said tag in said video
 stream, said tag including a category of said
 scene, a location for use in locating a beginning
 of said scene and a length of said scene, said
 tag having been so arranged as to prevent said
 tag from being used for commercial cutting;
 and
 means, responsive to a determination that said
 category coincides with said desired category,
 for clipping from said video stream a part of a
 length defined by said length of said scene
 from a position located by using said location in
 such manner as accords with said arrange-
 ment.

18. A system as defined in claim 16, wherein said
 means for making an arrangement comprises:

means for encoding said category into an
 encoded category through a one-way function;
 means for using said encoded category in
 place of said category; and
 means for sending, each of possible cate-
 gories, a set of said category and said encoded
 category to said second stations before insert-
 ing said tag in said video stream.

19. A system as defined in claim 17, wherein said cate-
 gory of said detected tag has been encoded into an
 encoded category with a one-way function, and
 wherein said means for clipping from said video
 stream a part of a length comprises:

means for receiving a set of said category and
 said encoded category for each of possible cat-
 egories; and
 means, responsive to a determination that said
 category of said detected tag coincides with
 said encoded category associated by said set
 with said desired category, for clipping from
 said video stream said part.

20. A system as defined in claim 16, or 18 wherein said
 encoded category is a syndrome of a combination

of said category and a parameter.

21. A system as defined in claim 20, further comprising:

means for making a list of subcategories for a 5
desired one of possible categories;
means for find a syndrome for a combination of
said desired category and each of said sub-
categories by using each of said subcategories
as said parameter; 10
means for send a table of said category, said
subcategories, and corresponding syndromes
to said second stations; and
means for using said syndromes as said
encoded categories. 15

22. A system as defined in claim 20, further comprising:

means for creating a super-category compris-
ing a list of categories; 20
means for find a syndrome for a combination of
said super-category and each of said list of cat-
egories by using each of said list of categories
as said parameter;
means for send said list for said super-category 25
to said second stations; and
means for using said syndromes as said
encoded categories.

**23. A system as defined in claim 17, or 19 wherein said 30
encoded category is a syndrome of a combination
of said category and a parameter.**

24. A system as defined in claim 23, further comprising:

means for receiving a table of said category, 35
subcategories of said category and corre-
sponding syndromes from said first station; and
means for using said syndromes as said
encoded categories and using said subcatego- 40
ries as said categories.

25. A system as defined in claim 23, further comprising:

means for receiving a super-category list com- 45
prising a list of categories from said first sta-
tion; and
means for using said syndromes as said
encoded categories and using said super-cate- 50
gory as one of said categories.

55

FIG. 1




FIG. 2

EXEMPLARY STRUCTURE OF A TAG




FIG. 5




FIG. 6




FIG. 3




FIG. 4





FIG. 7**FIG. 8**

AN EXEMPLARY COUNTERFEIT TAG

naEoia	10	1c
iozuw	11	
D	12	
10.0 SEC	13	
⋮		

FIG. 9

OPERATION OF THE COMPUTER 24




FIG. 10




FIG. 11







FIG. 12

440

CATEGORY (C _j)	ENCODED CATEGORY (f(C _j))
CAR	NC0iS3J
CAMERA	LAv0U3M
COSMETIC	Lg9LDEy
.....

FIG. 13

OPERATION OF THE COMPUTER 24

**FIG. 14****FIG. 15**





FIG. 18 540a

CATEGORY (C _j)	ENCODED CATEGORY (s(C _j)=X TH)
CAR	{SEDAN} TH CAR, {WAGON} TH CAR, {OUTDOOR} TH CAR
CAMERA	{NICON} TH CAMERA, {CANON} TH CAMERA, {KOTAK} TH CAMERA
SPORTING	{WARE} TH SPORTING, {OUTDOOR} TH SPORTING
...	...


FIG. 19 550

OUTDOOR	CAR, SPORTING, ...
---------	--------------------

FIG. 20 560

CATEGORY (C _j)	SUBCATEGORY (X)	X TH
CAR	SEDAN	{SEDAN} TH CAR
	WAGON	{WAGON} TH CAR

CAMERA	NICON	{NICON} TH CAMERA
	CANON	{CANON} TH CAMERA
	KOTAK	{KOTAK} TH CAMERA



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 926 892 A3

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
19.07.2000 Bulletin 2000/29

(51) Int. Cl.⁷: H04N 7/088

(43) Date of publication A2:
30.06.1999 Bulletin 1999/26

(21) Application number: 98310734.3

(22) Date of filing: 24.12.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 26.12.1997 JP 36893897
26.12.1997 JP 36893997


(71) Applicants:
• Matsushita Electric Industrial Co., Ltd.
Kadoma-shi, Osaka 571-8501 (JP)
• Information Broadcasting Laboratories, Inc.
Taito-ku, Tokyo 111-0035 (JP)

(72) Inventors:
• Kataoka, Mitsutero
Fujisawa-shi, Kanagawa-ken 251-0002 (JP)
• Machida, Kazuhiro
Inzai-shi, Chiba-ken 270-1356 (JP)
• Harada, Takenosuke
Tsuzuki-ku, Yokohama 224-0029 (JP)

(74) Representative:
Senior, Alan Murray
J.A. KEMP & CO.,
14 South Square,
Gray's Inn
London WC1R 5LX (GB)

(54) **Video clip identification system unusable for commercial cutting**

(57) A tagged scene of a video stream transmitted from a first to second stations in television broadcasting system is collected while preventing the tags from being used for commercial cutting (i.e., indiscriminate tagged scene cutting). The first station generates for each scene a tag includes a category, a location for use in locating a beginning of the scene and a length. A second station obtains a desired category from the user. Detecting a tag in the video stream, if the category coincides with the desired category, the second station clips from the video stream a part of the length defined in the tag from a position located by using the location. Five solutions are disclosed: removing the length information from tag; inserting counterfeit tags: the first station encoding a part of tag and the second station decoding the encoded part; the first station encoding the category and sending a category-encoded category table the second station; and a syndrome of a combination of said category and a parameter is used as an encoded category. The parameter may be used as subcategory and/or super-category.



EP 0 926 892 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 31 0734

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP 0 580 227 A (SOCIETA ITALIANA PER LO SVILUPPO DELL'ELETTRONICA) 26 January 1994 (1994-01-26) * abstract *	1,2,5-7, 16,17	H04N7/088
A	WO 97 49241 A (BEN-MOSCHE) 24 December 1997 (1997-12-24) * page 2, line 2 - line 24 *	1,2,16, 17	
A	EP 0 720 369 A (INTERNATIONAL BUSINESS MACHINES) 3 July 1996 (1996-07-03) * abstract * * column 7, line 28 - line 42 *	2,9,13, 17,19,23	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04N
Place of search		Date of completion of the search	Examiner
THE HAGUE		30 May 2000	Berwitz, P
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons</p> <p>&: member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 31 0734

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-05-2000

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 580227	A	26-01-1994	IT 1257390 B	15-01-1996
			DE 69326723 D	18-11-1999
			DE 69326723 T	16-03-2000
			ES 2140434 T	01-03-2000

WO 9749241	A	24-12-1997	NONE	

EP 720369	A	03-07-1996	US 5778135 A	07-07-1998
			CA 2155888 A	01-07-1996
			JP 8242440 A	17-09-1996

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)